



PC no	No req	Description	Used on
3	1	Drive pinion (large)	EL55 EL100/2500
4	1	Potentiometer pinion (small)	EL55 EL100/2500
5	1	Potentiometer spacer	EL55 EL100/2500
6	1	Potentiometer 10K Ohm	EL55 EL100/2500
9	3	Printspacer	EL55
9	3	Spacer/screw	EL100/2500
16	1	Position transmitter board	EL55 EL100/2500

Description

This electric actuator variation provides a continuous position indication by transmitting a 4 to 20 milli-Amp signal, this is proportional to the output shaft position.

This 4 wire version consists of a potentiometer and an electronic card complete with a dual voltage (AC.) power transformer, fed from the actuator's own incoming power supply. The remaining two wires are used for the output position signal.

The card is equipped with trimmers for zero and span adjustment and terminals for the internal and external connections.

Construction

The potentiometer and circuit board located on the top motor plate are wired as shown, using the board's own terminal strip.

Specification

Input : 120 or 220 V 50/60 Hz.
Output : 4 to 20 mA, with adjustable zero and span
Temperature : -4°F to +158°F.
Potentiometer : 10KΩ (see sheet 5.202).

Identification

Factory Option : Add "+ PT4" to the basic actuator size.
: eg. EL100 120/60 + PT4
Kit Option : Actuator size is added to: "Kit, PT4"
: eg. Kit, PT4/EL55 220/50

- Note**
- 1) When supplied as a kit option, all the components as shown are included, together with an instruction sheet.
 - 2) Wiring diagram is shown with actuator in mid position.
 - 3) Wiring diagram for EL55 120V/60Hz + PT4

